

Minoura Trainer Tire Size Capacity Chart

(Revised: October 1, 2015)

Diamete	Tire size	inch	(ETRTO)	LR960,LR760		LR340		B60-R		QUATTRO-C	LR240	RDA80	RDA29er	
Installing Z- Adaptor				Yes	No	Yes	No	Yes	No					
Tire Outer Diameter Range (mm)				530 - 652	632 - 704	512 - 678	600 - 714	522 - 688	608 - 726	568-704	394 - 512	568 - 663	568 - 742	
427	17 x 1-1/4	18 #	32-369											
427	18 x 1.50		40-355											
430	18 x 1.75	20 #	47-355											
466	20 x 1.25 (406)		32-406											
474	20 x 1.50	24 #	40-406											
511	20 x 1-1/8 (451)		28-451											
515	20 x 1-3/8	26 #	37-406											
563	22 x 1-3/8		37-490											
568	24 x 3/4 Tubuler	24 #	25-520											
602	24 x 1.75		44-507											
609	26 x 1.00	26 #	25-559											
613	24 x 2.00		50-507											
619	650 x 23C	700C	23-571											
640	26 x 1.50		40-559											
644	26 x 1.75	700C	47-559											
659	700 x 18C		18-622											
663	26 x 2.35	700C	60-559											
666	650 x 35A		35-590											
667	700 x 23C	700C	23-622											
670	650 x 38B		40-584											
677	650 x 38A	700C	40-590											
680	700 x 28C		28-622											
686	700 x 32C	29	32-622											
694	700 x 38C		40-622											
700	700 x 40C	700C	42-622											
714	700 x 45C		47-622											
729	29 x 2.10	29 (Fat/Knobby)	54-622											
742	29x2.35		60-622											
752	29 x 2.55		65-622											

Note: We **don't recommend** to use the Z-adaptor when using 26x1.50 (40-559) – 650x38A (40-590) on LR340 (shown as gray zone).
The tire may conflict with the plastic part of the Mag unit and cause damages.

Note: Each tire brand has its own size. Even if the tire shows the same size, the actual diameter must be different.
 We don't guarantee the above compatibility. You need to measure the actual diameter of your tire before using on our trainer.